

Inside Module 4

Selecting Records with Suprtool	<u>Page</u>
<input type="checkbox"/> Using the If command	2
<input type="checkbox"/> Comparing fields	4
<input type="checkbox"/> Selecting by pattern-matching	7
<input type="checkbox"/> Let's do a crossword puzzle	9
<input type="checkbox"/> Dates as selection criteria	10
<input type="checkbox"/> Selecting on partial fields	18
<input type="checkbox"/> Using tables to select records	23
<input type="checkbox"/> Using Tables with Keyed reads	32

Selecting records

- You can use the IF command to choose records by selecting ranges of numbers, dates, or multiple criteria

```
>if sales-qty >= 100 and sales-qty < 5000
```

```
>if cust-status = 10,20,30,35
```


- Only *one* IF command is permitted per task

- Suprtool uses short-circuit evaluation. e.g.

```
>if age > 70 and sex = "M"
```

should be faster than:

```
>if sex = "M" and age > 70
```



More options to specify selection criteria

You can also use these words and signs to select records:

- AND, OR and NOT operators
- parentheses:) or (
- relational operators: = < > >= <= <>
- pattern matching: == and ><

OR

NOT

AND

Comparing fields

- You can compare one field to another


```
>if deliv-date = purch-date
```

- You can compare a numeric field to a calculation

```
>if sales-total <> product-price * sales-qty
```

- You can compare a field to a constant

```
>if cust-status = "OK", "DEAC"
```



Arithmetic If expressions

- Select records based on arithmetic expressions


```
>if unit-cost * sales-qty > 10000
```

```
>if sales-total < sales-qty * product-price + sales-tax
```

- Use parentheses to keep things clear

Field types and sizes in comparisons


- Byte and character fields can be different sizes, but...
 - comparison is for length of shorter field
 - comparison ignores last bytes of longer field



Selecting records by pattern-matching

Pattern-matching

- Includes or excludes values in specified fields using these operators
 - == selects records that match pattern
 - >< selects records that do not match pattern
- Can be used only on character fields
- Can specify multiple selection criteria
- Can use special characters to define selection criteria



Special characters in pattern-matching

□ Use these special characters to match patterns:

@ represents any *string* of characters

? represents one *alphanumeric* character

represents one *numeric* character

~ represents zero or more *blanks*

& indicates the next character is *literal*

Exercise 1

Solve a crossword puzzle

- Use Suprtool to solve this crossword puzzle:
 - an 8 letter word
 - meaning “most befuddled or dazed”
 - second letter is an “o”
 - fourth letter is a “z”
- HINT: Suprtool has a spelling checker. Each word in its dictionary is stored as one record.



Identifying a field as a date

- First use the ITEM command to identify a field as a date:

```
>item transaction-date,date,mmddy
```

```
>item date-of-birth,date,phdate
```

```
>item disbursement-date,date,ccyymmdd
```

- Then use the IF command to select records:

```
>if transaction-date = $today and &  
date-of-birth < $date(1950/01/01) &  
and disbursement-date >= &  
$date(*+5/*/*)
```

1999						
			1	2	3	4
5	6	7	8	9	10	11
12	13	14	15	16	17	18
19	20	21	22	23	24	25
26	27	28	29	30	31	

\$DATE - Supported Date Formats

1. YYMMDD
YYYYMMDD / CCYYMMDD
MMDDYY
MMDDYYYY
DDMMYY
DDMMYYYY
2. YYMM
YYYYMM / CCYYMM
MMYYYY
3. CCYY
4. YYMMDD
5. AAMMDD
AAMM
MMDDAA
DDMMAA
6. YYDDD
CCYYDDD
7. ASK, Calendar, HPCalendar, Oracle, PHDate, SRNChronos

Dates as selection criteria

- You can select records by specifying date criteria

```
>item purch-date,date,phdate
```

```
>if purch-date = $date(98/11/30) {Nov. 30, 1998}
```

- You can also select a range of dates (e.g., all of December 1998)

```
>if purch-date > $date(98/11/30) and &  
purch-date < $date(99/01/01)
```

```
>if purch-date >= $date(98/12/01) and &  
purch-date <= $date(98/12/31)
```

Choosing records by relative date

- The \$TODAY function optionally accepts an argument that indicates the number of days before or after the current day

```
>item expiry,date,yymmdd
```

```
>if expiry = $today {today}
```

```
>if expiry = $today(-1) {yesterday}
```

```
>if expiry > $today(+14) {more than 2 weeks away}
```

- Suprtool converts the \$DATE function into a constant

```
>item date-field,date,mmddyy
```

```
>if date-field = $date(*/*-6/*) {six months ago}
```

```
>if date-field = 091898 {if today is Mar. 18, 1999 (constant)}
```

Dates must collate correctly for > and <

- \$DATE gets converted to a constant
- For ddmmyy or mmddyy dates, the constant is in that format
- ddmmyy and mmddyy dates don't sort properly
- Suprtool rejects greater than or less than comparisons for them
- Error: Invalid date format for the comparison
- Use \$STDDATE for non-collating dates

Use *\$STDDATE* for non-collating dates

- Turn a non-collating date into CCYYMMDD format:

```
>item purch-date,date,mmddy  
>if $stddate(purch-date) < $today
```
- Compare dates in two different formats by converting them both to CCYYMMDD format:

```
>item purch-date,date,mmddy  
>item deliv-date,date,ddmmyyyy  
>if $stddate(purch-date) <= $stddate(deliv-date)
```
- Dates must be valid for \$stddate to work:

```
>item purch-date,date,mmddy  
>if not invalid(purch-date) and &  
$stddate(purch-date) < $today
```

Date Arithmetic

- You can calculate the difference between 2 dates using the **\$days** function
- **\$days** converts a date to the **juliandays** date format. I.e. the number of days since a base date (4713 BC)

```
item purch-date,date,YYYYMMDD
```

```
item deliv-date,date,YYYYMMDD
```

```
if $days(deliv-date) - $days(purch-date) > 5
```

- Invalid dates return value 0 (zero)

Converting days back to dates

- **Juliandays** date format represents days offset from 4713 BC
- Combine **juliandays** with **\$stddate** to convert result of **\$days** calculations:

```
>....
```

```
>extract latest-delivery = ($days(date-ord) + 7)
```

```
>xeq
```

```
>...
```

```
>item latest-delivery,date,juliandays
```

```
>item deliv-date,date,YYYYMMDD
```

```
>extract deliv-date = $stddate(latest-delivery)
```

Verify that dates are valid

- Use \$INVALID to select records with invalid dates

```
>item purch-date,date,yymmdd
>if $invalid(purch-date)
>list standard title "Records with bad dates"
```
- Or use it to deselect invalid dates

```
>if not $invalid(purch-date) and &
purch-date > $date(*/*-6/*)
```

Year 2000 dates

- Some selections generate “invalid” date constants, if the date field cannot hold century information and the constant would be in the next century

```
>item purch-date,date,yymmdd
>if purch-date > $date(*+5/*/*)
Error: Cannot use a date beyond 1999 for this format
```
- You can override this error condition

```
>set date ifyy2000error off
```
- Or you can use \$STDDATE to assume a century

```
>set date cutoff 50
>if $stddate(purch-date) > $date(*+5/*/*)
```

\$truncate, Mod mod and \$abs functions

- **\$truncate** returns “whole number”, I.e. drops decimals
`$truncate(127.2 / 12) = 10`
- **Mod** returns the remainder
`7 mod 5 = 2`
- **\$abs** returns the absolute value (no sign)
`$abs(-121) = 121`

Selecting on parts of a number

- You can select any part of a numeric field with the If command
- Use a divide operation to select on the high-order digits
`>if $truncate(ord-date-yymmdd / 100) = 9812`
- Use MOD to select on the low-order digits
`>if ord-date-yymmdd mod 100 <= 15`
- Use divide and MOD together to select on middle digits
`>if ($truncate(ord-date-yymmdd / 100) mod 100) <= 02`

Calculating day of week

- Juliandays measures offset from a Monday
- Combine \$days with mod to calculate day-of-week
>ite ord=date,date,YYYYMMDD
>ext day = (\$days(dt) mod 7)

0 = Monday

1 = Tuesday

2 = Wednesday

.....

6 = Sunday


Comparing sub-fields

- You can select any part of a character field with the IF command
- If we define a street-address field as 2X25, any part of this field can be selected

```
>if street-address(2) = "Canada"
```

```
>if street-address(1,7,2) = "10"
```

```
>if street-address(1,13) = "Marine Drive"
```



Testing byte type fields

- You can test if a byte type field contains alpha, numeric, alphanumeric or special characters

```
>if cust-account = numeric
```

```
>if street-address <> alphanumeric
```

- You can also check for an ASCII character by specifying its numeric value or control letter

```
>define any-char,1,1,byte
```

```
>if any-char = ^13           {if byte is a Return}
```

```
>if any-char = ^G           {if byte is a Bell}
```



Checking bits within a field

- The IF command can select records based on bit values in a field

```
>if cust-status.(3:1) = 1
```

```
>if cust-status.(3:2) = 0
```

- Bit checking only works for 16-bit words




- Field must be *Integer* or *Logical*

Extending the If command

- You can extend the length of an IF command beyond the 256 character limit by using the \$READ function

```
>get m-customer
>if $read
-name-last == "@Kirk@" and
-state-code = "BC"
-and
-cust-account >
-12
-//
```



- \$READ prompts for the next line of the IF expression until it encounters a Return or a double slash (//)

Creating tables as selection criteria

- The TABLE command creates a set of values that can be used as selection criteria:

TABLE *tablename, itemname, table-keyword, table-values*


```
>table select,transcode,item,"BUY","SELL"
```

```
>table cust-table,cust-num,file,custfile
```

- The source of input can be an item value or a file
- The TABLE command sorts values as they are loaded into a table


Table characteristics

- Only *one key* can be put into a table
- Suprtool can handle up to *ten tables*
- Each table can have up to *two gigabytes* of data on MPE
- 500 Mbs in total on HP-UX
- Tables are *temporary* structures that are reset when a task has been completed
- You can *hold* a table so it is not reset
- Table values are *sorted*



When would I use a table?

- Instead of listing all the values
 `>if field = value1,value2,value3`
- When there are too many values to fit in an IF command
- When the selection values change occasionally
- When the selection is based on the results of a prior task



Loading a table with values from a file

- If the file containing the values is not sorted, specify FILE as the keyword

```
>table states,st-code,file,western.data
```

```
>if qty-ship < qty-order and $lookup(states,st-code)
```

- If the file is sorted, specify SORTED as the keyword


```
>table states,st-code,sorted,western.data
```

```
>if qty-ship < qty-order and $lookup(states,st-code)
```

- The field selected from the input file must have exactly the same format as the table

How does the Table command find a field?

- If the input file is self-describing, Suprtool finds the location of the field via the user label
- If the file is not self-describing, or the named field is not found in the file label, Suprtool loads the requested data from the start of each record



Inserting items into a table

- You can also use the TABLE command to insert hardcoded values
- Specify ITEM as the table keyword
 - >table states,st-code,item,"WA","OR","CA"
 - >table states,st-code,item,"WI","ID","NE"
 - >table states,st-code,item,"NM","AK","HI"
 - >if cust-status = "OK" and \$lookup(states,st-code)

Selecting input records that match a value in a table

- Use the \$LOOKUP function with the IF command to select records that match a value in a table

```
>if $lookup(cust-table,cust-acct)
```



- If the \$LOOKUP function finds a match, the expression is true
- If there are multiple conditions in the IF expression, the expression is evaluated faster when \$LOOKUP is the last condition

```
>if status = "10" and $lookup(cust-table,cust-acct)
```

- Use NOT to select records which don't match table values

Lookup and Data

```
>get ord-details
```

```
>table cust-table, cust-no, file, custlist,data(state-code)
```

```
>if $lookup(cust-table, cust-no, state-code) = state-code
```

```
>output orders
```

```
>xeq
```

Saving and deleting tables

- The HOLD option tells Suprtool to save a table after a task has been completed

```
>table states,st-code,file,western.data
```

```
>table parts,part-no,file,partin,hold
```

- The RESET TABLE command clears all the tables. You cannot reset individual tables.


```
>reset table
```

Can we find all the invoices for BC customers and sort them by customer ID?

- The invoice records are in the sales detail dataset, but state-code is in the customer master record

```
>get m-customer
>if state-code = "BC"
>extract cust-account
>output bccust
>xreq

>table bc,cust-account,file,bccust
>get d-sales
>if $lookup(bc,cust-account)
>sort cust-account
>list standard
>xreq
```



Selecting records using the Chain command

- Alternately, you can use the CHAIN command to find the required invoices after you have created an output file of British Columbia customers (Bccust)

```
>table brit,cust-account,file,bccust
```

```
>chain d-sales,cust-account=brit
```


```
>list standard
```

```
>xeq
```

- The CHAIN command performs keyed retrievals for the values in the table.
- No SORT command is necessary because the CHAIN command retrieves the records in the same order as they are found in the table

String Functions and Features

- \$TRIM,\$RTRIM,\$LTRIM
- \$UPPER,\$LOWER
- + Operator and Target field



Summary

- IF command
- Field comparison
- IF expressions (Boolean operators, parentheses)
- Pattern-matching
- Date fields
- Sub-field comparisons
- \$READ function
- Tables
- Selecting from one file based on criteria in another file